

64331 FL-AC 30W

6.6 A Current Controlled Halogen - Reflector Lamps for Series Operation



Areas of application

- Airfield Lighting

Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistance to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Technical data

General Product Information

Product number (Americas)	58938
Product name (Americas)	6.6A 30MR16 64331AC FL 20/CS 1/SKU
Lamp type	SINGLE ENDED
Global order reference	64331 FL-AC 30W


Electrical Data

Nominal wattage	30 W
Nominal current	6.6 A
Type of current	AC

Photometric Data

Color rendering index Ra	100
--------------------------	-----

Physical Attributes & Dimensions



Connector B, female round



Connector A, female

Lamp base	Leads w/male and female flat c
Diameter (in)	1.984 in
Diameter	50.4 mm
Length	48.0 mm
Connector: presence	Yes
Connection with cable	Yes
Product weight	25.00 g

Lifetime Data

Nominal lifetime	1000 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Declaration no. in SCIP database	In work

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.