

64333 C 40-15

6.6 A Current Controlled Halogen - Reflector Lamps for Series Operation




Areas of application

- Airfield Lighting

Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistance to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



Product datasheet

Technical data

General Product Information

Product number (Americas)	4008321104885
Product name (Americas)	6.6A 40W MR11 64333C 20/CS 1/SKU
Global order reference	64333 C 40-15


Electrical Data

Nominal wattage	40 W
Nominal current	6.6 A

Photometric Data

Nominal luminous flux	10000 lm
Axial luminous intensity	12700 cd
Color temperature	3400 K

Physical Attributes & Dimensions



Lamp base	Leads w/male flat connectors
Diameter	35.3 mm
Length	35.0 mm
Length with base excl. base pins/connection	37.00 mm
Connector: presence	Yes
Connection with cable	Yes
Mains terminals	Leads w/male flat connectors
Product weight	15.00 g

Operating Conditions

Burning position	h45
------------------	-----

Product datasheet

Lifetime Data

Nominal lifetime	1500 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321104885
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321104885	OSRH64333C	-	-	-
4008321104885	OSRH64333C	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321104885	64333 C 40-15	Folding carton box 1	34 mm x 34 mm x 50 mm	0.06 dm ³	19.00 g
4008321104892	64333 C 40-15	Shipping carton box 20	191 mm x 81 mm x 130 mm	2.03 dm ³	468.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.