

6.6A 45W MR16 64337A 45-15 20/CS 1/SKU



Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistance to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield Lighting

Technical data

General Product Information

Product number (Americas)	58907
Product name (Americas)	6.6A 45W MR16 64337A 45-15 20/CS 1/SKU
Lamp type	SINGLE ENDED
Global order reference	64337 A 45-15


Electrical Data

Nominal wattage	45 W
Nominal current	6.6 A
Type of current	AC

Photometric Data

Nominal luminous flux	19000 lm
Axial luminous intensity	21000 cd
Color temperature	3200 K
Color rendering index Ra	100

Physical Attributes & Dimensions



Connector A, female

Lamp base	Leads w/female flat connectors
Diameter (in)	1.984 in
Diameter	50.4 mm
Length	45.0 mm
Length with base excl. base pins/connection	45.00 mm
Connector: presence	Yes
Connection with cable	Yes
Mains terminals	Leads w/female flat connectors
Product weight	31.00 g

Product datasheet

Operating Conditions

Burning position	Horizontal
------------------	------------

Lifetime Data

Nominal lifetime	1500 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321102515
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58907	4008321102515	FOLDING BOX	1	2.0 in x 2.0 in x 2.4 in	0.1 lb
58907	4008321102720	SHIPPING BOX	20	10.1 in x 4.3 in x 5.2 in	2.0 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.