

# 64340

## 6.6 A Current Controlled Halogen - Double End Lamps for Series Operation



### Areas of application

- Airfield Lighting

#### Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistence to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free





## Product datasheet

#### Technical data

### **General Product Information**

LIF code	J1/82
Global order reference	64340


### **Electrical Data**

Nominal wattage	100 W
Nominal current	6.6 A

### **Photometric Data**

Nominal luminous flux	2170 lm
Color temperature	2900 K

## **Physical Attributes & Dimensions**



Lamp base	R7s-15
Diameter	51.0 mm
Length	65.6 mm
Length with base excl. base pins/connection	65.00 mm
Product weight	6.00 g

## **Operating Conditions**

Burning position	Horizontal
------------------	------------

### **Lifetime Data**

Nominal lifetime	1000 hr

### **Environmental & Regulatory Information**

## Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4050300017266			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

### Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300017266	OSRH64340	-	4739724	-

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300017266	64340	Folding carton box 1	113 mm x 33 mm x 33 mm	0.12 dm <sup>3</sup>	19.00 g
4050300209098	64340	Shipping carton box 25	180 mm x 130 mm x 180 mm	4.21 dm <sup>3</sup>	510.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.