

## 64361 HLX-A150-15

### 6.6 A Current Controlled Halogen - Pk30d Base Lamps for Series Operation



---


#### Areas of application

- Airfield Lighting

---

#### Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistance to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



# Product datasheet

## Technical data

### General Product Information

Product number (Americas)	59077
Product name (Americas)	64361 HLX-A 150-15 PK30D 100/CS 1/SKU
LIF code	J1/83
Global order reference	64361 HLX-A 150-15



### Electrical Data

Nominal wattage	150 W
Nominal voltage	22.7 V
Nominal current	6.6 A

### Photometric Data

Nominal luminous flux	3600 lm
Color temperature	3100 K
Light center length (LCL)	20.0 mm
Light center length (LCL) - (in)	0.787 in

### Physical Attributes & Dimensions



Connector A, female

Lamp base	PK30d
Diameter (in)	0.531 in
Diameter	13.5 mm
Length	50.0 mm
Length with base excl. base pins/connection	35.00 mm
Connector: presence	Yes
Product weight	14.50 g

### Operating Conditions

## Product datasheet

Burning position	s90
------------------	-----

### Lifetime Data

Nominal lifetime	1500 hr
------------------	---------

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321345691
Declaration no. in SCIP database	d0b74040-bc55-40f6-8ef2-40462d44a388
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

## Product datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321345691	64361 HLX-A150-15	Folding carton box 1	32 mm x 37 mm x 71 mm	0.09 dm <sup>3</sup>	22.00 g
4008321345707	64361 HLX-A150-15	Shipping carton box 100	341 mm x 191 mm x 154 mm	10.03 dm <sup>3</sup>	2341.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---