

64380

6.6 A Current Controlled Halogen - Double End Lamps for Series Operation




Areas of application

- Airfield Lighting

Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistance to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



Technical data

General Product Information

Lamp type	SINGLE ENDED
LIF code	J1/40
Global order reference	64380


Electrical Data

Nominal wattage	200 W
Nominal current	6.6 A
Type of current	AC

Photometric Data

Nominal luminous flux	4400 lm
Color temperature	2800 K
Color rendering index Ra	100

Physical Attributes & Dimensions



Lamp base	R7s-18
Diameter (in)	0.591 in
Diameter	15.0 mm
Length	65.6 mm
Length with base excl. base pins/connection	65.00 mm
Product weight	6.00 g

Operating Conditions

Burning position	p15
------------------	-----

Lifetime Data

Product datasheet

Nominal lifetime	1000 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300209944 0046135587078
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300209944	OSRH64380	-	4739726	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300209944	64380	Folding carton box 1	113 mm x 33 mm x 33 mm	0.12 dm ³	17.33 g
4050300209951	64380	Shipping carton box 25	180 mm x 130 mm x 180 mm	4.21 dm ³	565.33 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.